BOOMER[™] COMPACT TRACTOR 24 HP



BOOMER 24



YOUR JOBS - NOW MADE EASIER

This Boomer[™] 24 compact tractor is the ultimate power tool for homeowners, rural lifestylers, landscapers and hobby farmers. Responsive, efficient and comfortable, they're built to make your jobs easier.

THE POWER YOU NEED

Quiet, fuel-efficient Tier 4 3-cylinder engines give you the power you need for loading, mowing, digging, blowing snow, tilling and much more. You get fast implement and steering response thanks to the high-capacity hydraulic system.

OPERATING EASE

The word "easy" defines Boomer tractors. Controls come easily to hand, and the large, uncluttered operating platform gives you plenty of legroom to stretch out. Controls are color-coded and clearly marked so you are confident of your every move.

SMOOTH SPEED CHANGES

The Boomer 24 is equipped with a 2-range hydrostatic transmission. It makes direction changes even easier with a new dual pedal design. Push one pedal to go forward, push the second pedal to go backward. No clutching or hand shifting is required. You also get the convenience of cruise control as a standard feature.

PROVEN MANEUVERABILITY AND TRACTION

Your Boomer tractor is designed to get you in and out of tight spots and maneuver easily around and — thanks to generous ground clearance — over obstacles. Four-wheel drive gives you the traction you need to get through rough patches. When the going gets tough, simply step on the differential lock foot pedal and both rear wheels lock together for added traction to get through snow, mud or rough, slippery ground.

SIMPLE SERVICE

Boomer tractors are a snap to maintain. Checkpoints are easy to reach and the flip-up hood gives you complete access to the engine, battery, radiator and air filters.

BOOMER[™] 24 COMPACT TRACTOR SPECIFICATIONS

BOOMER 24

ENGINE Gross horsepower, hp (kw) Rated speed (rpm) Type Displacement, cu. in. (L) Air cleaner Fuel tank, gal. (L) Alternator, amps	24.4 (18.2) 2700 3-cylinder diesel Tier 4 80.4 (1.3) Single replaceable dry element 6.6 (25) 50
PTO PTO HP (HST), hp (kw) PTO speed (rpm) PTO type	Standard rear and mid PTO 18.5 (13.8) 540 rear/2000 mid PTO Electro-hydraulic engaged; independent
TRANSMISSION Type, Mechanical/hydrostatic Maximum forward speed, HST – mph (kph), R4 Cruise control Rear diff. lock engagement Brake type	HST+2 range 11.3 (18.6) Standard Mechanical/foot Mechanical/wet, multi disc
HYDRAULICS Implement hydraulic flow, gal. (lpm) Steering hydraulic flow, gal. (lpm) Remote valve 3-point lift capacity @ ball ends, gal. (lpm) 3-point linkage category Steering type	6.7 (25.5) 2.9 (11) Optional DIA 1433 (650) 1 Hydrostatic
DIMENSIONS (w/R4 tires) Wheel base, in. (cm) Length, in. (cm) Height (ROPS), in. (cm) Width, in. (cm) Weight (HST), lbs. (kg) Tire choice	59 (150) 103.6 (263.2) 85.5 (217.3) 49.1 (124.7) 1708 (775) R3 turf tread or R4 industrial tread



We've got your back with the FREE Boomer Guard 5 Limited Warranty. It provides 5 years of worry-free operation, including 2 years of bumper-to-bumper coverage plus an extra 3 years of powertrain protection. You won't find a better compact tractor or warranty anywhere.

READY FOR ANY JOB

Whether you need to load mulch, mow the lawn, clear a pasture, dig a trench, till the garden, move snow, clean stalls or install a fence, Boomer tractors are for you. These tractors make it easy to change implements so you can move quickly from job to job.

- Category I three-point hitch
- One optional rear hydraulic remote
- Independent, electro-hydraulic 540-rpm rear PTO
- Standard electro-hydraulic independent mid-PTO to power mid- and front-mount implements
- Many accessories, implements and attachments to match your needs

FRONT LOADER MODEL	235TL
Lift capacity @ max. height @ pins, lbs. (kg)	1034 (470)
Breakout force @ pins, lbs. (kg)	1672 (760)
Maximum lift height @ bucket pivot pin, in. (cm)	80.7 (205)
Maximum dump angle – degrees	51°
Bucket rollback angle – degrees	29°

NOTES: Specifications based on ASAE (S301.3) and are subject to change without notice. Dimensional and performance specifications are based on typical tractors and tire sizes.



Open, spacious operator's platform gives you lots of legroom.



Rear PTO and 3-point hitch allow you to attach countless implements to any job.



Learn more at www.newholland.com/na

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

© 2014 CNH America LLC. All rights reserved. New Holland and CNH Capital are registered trademarks of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.